

BB-4012F

Box and Pan Brake

40" (1016mm) Length, 12 GA (2.75mm) MS

SPECIFICATIONS	Imperial	Metric
Length	40"	1016mm
Thickness (SS)	12 ga (.1054"/2.6mm)	16 ga (.0595"/1.6mm)
Bend Angle	0 - 135°	
Max Clamping Bar Lift (Foot Operated)	1.85"	47mm
Box Depth	4"	102mm
Shipping Dimensions (L / W / H)	58" / 25" / 50"	1474 / 635 / 1270mm
Shipping Weight	705 Lbs	320 Kg

Specifications subject to change without notice.



Foot operated material clamping
Enables easy material adjustment
Stop rod for repeatable bending
Hardened finger assortment (1 pc. each size):
25, 30, 35, 38, 45, 50, 76, 102, 150, 197, 270mm

BB-5014F

Box and Pan Brake

50" (1270mm) Length, 14 GA (2mm) MS

SPECIFICATIONS	Imperial	Metric
Length	50"	1270mm
Thickness (SS)	14 ga (.0747"/2mm)	20 ga (.0355"/1mm)
Bend Angle	0 - 135°	
Max Clamping Bar Lift (Foot Operated)	1.85"	47mm
Box Depth	4"	102mm
Shipping Dimensions (L / W / H)	67" / 28" / 50"	1702 / 711 / 1270mm
Shipping Weight	800 Lbs	365 Kg

Specifications subject to change without notice.

Foot operated material clamping
Enables easy material adjustment
Stop rod for repeatable bending
Hardened finger assortment (1 pc. each size):
25, 30, 35, 38, 45, 50, 76, 102, 150, 197, 254, 270mm



NEW