

# DP-1000VS

Variable-Speed Drill Press

SPECIFICATIONS	Imperial	Metric
Drill Capacity	1"	25mm
Tapping Capacity	5/8"	16mm
Spindle Speeds	150-3000rpm	
Swing	16"	406mm
Spindle Taper	MT3	
Spindle Travel	5.3"	135mm
Spindle Nose to Table	23.8"	605mm
Spindle Nose to Base	45.3"	1151mm
Quill Diameter	2.44"	62mm
Column Diameter	3.62"	92mm
Table Dimensions (L/W)	18.1" / 14.2"	460mm / 361mm
Table Slot	5/8"	16mm
Base Dimensions (L/W)	27" / 19"	686mm / 483mm
Main Motor	2HP	1.5kw
Coolant Motor	.125 HP	.1 kw
Power Requirement	240V, Single Phase, 50Hz	
Shipping Dimensions (L/W/H)	32" / 24" / 79"	813mm / 610mm / 2007mm
Shipping Weight	579 lbs	263 Kg

Specifications subject to change without notice.



- Variable-speed inverter-driven head
- Manual feed
- Utilizes MT #3 spindle taper
- Digital RPM readout
- Integrated coolant system
- Swing-away safety guard
- Large adjustable work table with machined vise / holder slots