

DP-1250VS

Variable-Speed Drill Press



SPECIFICATIONS	Imperial	Metric
Drill Capacity	1.25"	32mm
Tapping Capacity	0.75"	19mm
Spindle Speed high	245-2000rpm	
Spindle Speed Low	85-540rpm	
Swing	20.8"	528mm
Spindle Taper	MT4	
Spindle Travel	5.9"	150mm
Spindle Nose to Table	36.41"	925mm
Spindle Nose to Base	48.22"	1225mm
Quill Diameter	2.95"	75mm
Column Diameter	4.52"	115mm
Table Dimensions (L/W)	22"/18.5"	559mm / 470mm
Table Slot	5/8"	16mm
Base Dimensions (L/W)	27"/19"	686mm / 483mm
Main Motor	2HP	1.5kw
Coolant Motor	.125 HP	.1kw
Power Requirement	240V, Single Phase, 50Hz	
Shipping Dimensions (L/W/H)	40"/25"/83"	1016mm/635mm/2108mm
Shipping Weight Lbs /Kg	847 Lbs	384Kg

Specifications subject to change without notice.

- Variable-speed inverter-driven head
- Manual feed
- Utilizes MT #4 spindle taper
- Digital RPM readout
- Integrated coolant system
- Swing-away safety guard
- Large adjustable work table with machined vise / holder slots
- Worklight as Standard