

DP-1500VS

Variable-Speed Drill Press

SPECIFICATIONS	Imperial	Metric
Drill Capacity	1.5"	38mm
Tapping Capacity	15/16"	24mm
Spindle Speed High	245-2000 rpm	
Spindle Speed Low	85-540 rpm	
Swing	20.8"	528mm
Spindle Taper	MT4	
Spindle Travel	5.9"	150mm
Spindle Nose to Table	22.75"	578mm
Spindle Nose to Base	40.75"	1035mm
Quill Diameter	2.95"	76mm
Quill Feed (3 speeds)	.198, .102, .051, mm/rev	
Column Diameter	4.52"	115mm
Table Dimensions (L/W)	22"/18.5"	559mm / 470mm
Table Slot	5/8"	16mm
Base Dimensions (L/W)	27"/19"	686mm / 483mm
Main Motor	2HP	1.5kw
Coolant Motor	.125 HP	.75kw
Power Requirement	240V, single Phase, 50Hz	
Shipping Dimensions (L/W/H)	40"/25"/83"	1016mm/635mm/2108mm
Shipping Weight Lbs /Kg	902 Lbs	409Kg

Specifications subject to change without notice.



- Variable-speed inverter-driven head**
- 3-speed power down feed**
- Utilizes MT #4 spindle taper**
- Auto reverse tapping feature**
- Digital RPM readout**
- Integrated coolant system**
- Swing-away safety guard**
- Large adjustable work table with machined vise / holder slots**