

R-H120

Roll Bender
Double-Pinch Hydraulic

SPECIFICATIONS	METRIC	
Capacities	Size (mm)	Min Diameter (mm)
Pipe	114mm x 6mm	1854mm
Round Tube	140mm (3mm)	2997mm
Square Tube	102mm (5mm)	2997mm
Angle Iron	102mm (10mm)	1600mm
Solid Square	60mm	1016mm
Solid Round	70mm	813mm
FLAT BAR		
Easy Way	200mm (35mm)	1017mm
Hard Way	102mm (25mm)	1600mm
ROLL DIAMETER		
Upper	315mm	
Lower	315mm	
Roll Adjustment	Hydraulic	
Pinch	Double - Independant	
Shaft Diameter	100mm	
Driven Rolls	3	
Digital Readout	Yes	
Speeds	5.4 rpm	
Motor	11kw	
Power Requirement	415V, Three Phase, 50Hz	
Shipping Dimensions (L/W/H)	1600mm/1473mm/1803mm	
Shipping Weight	2257 Kg	
Shaft Diameter	100mm	3.937mm
Roll Diameter	315mm	12.40mm
Double Pinch	Double	

Specifications subject to change without notice.

127mm x 6.5mm pipe capacity
Double pinch
Hydraulic lateral angle guide rolls
Horizontal or vertical bending
Overload protected
Hydraulic drive

NEW

