

RDB-125

Rotary Draw Bender

63mm x 3mm Mild Steel Tube Capacity

SPECIFICATIONS	Imperial	Metric
Mild Steel Pipe (Schedule 40)	2.00"	60mm x 4mm
Aluminium Pipe (Schedule 40)	2.00"	60mm x 4mm
Stainless Steel Pipe (Schedule 40)	1.50"	48mm x 3mm
Mild Steel Round Tube (Wall)	2.50" (.125)	63mm x 3mm
Aluminium Round Tube (Wall)	2.50" (.156)	63mm x 4mm
Stainless Steel Round Tube (Wall)	2.30" (.125)	60mm x 3mm
Chromolly Round Tube (Wall)	2.00" (.125)	51mm x 3mm
Mild Steel Solid Rod	1.25"	32mm
Mild Steel Square Tube (Wall)	2.00" (.125)	51mm x 3mm
Minimum OD	0.25"	6.3mm
Maximum Speed to 180°		40Sec
Maximum Center Line Radius (CLR)*	10.50"	267mm
Minimum CLR	.50"	13mm
Power Requirements	220V, Single Phase, 50Hz	
Weight (Lbs.)	350	160Kg
Length	42.00"	1067mm
Width	22.00"	559mm
Height	42.00"	1067mm

Specifications subject to change without notice.



Low-pressure industrial-grade hydraulics



Shown with optional tooling



Easy-to-read degree of bend indicator