

SBR-3020

3-in-1 Combination Shear, Brake,
Roll - 30" (762mm) Length, 20 GA (1mm) MS

SPECIFICATIONS	Imperial	Metric
Bed Width	30"	762mm
Shear Capacity	20ga (.0359")	1mm
Bending Capacity	20ga (.0359")	1mm
Rolling Capacity	20ga (.0359")	1mm
Max Bend Angle	90°	
Min. Rolling Diameter	1.5"	38mm
Power Requirement	Manual	
Shipping Dimensions (L/W/H)	38"/18"/27"	965mm/457mm/686mm
Shipping Weight	363Lbs	165Kg
Box Depth	4"	102mm

Specifications subject to change without notice.



Wire Grooves

SBR-4020

3-in-1 Combination Shear, Brake,
Roll - 40" (1016mm) Length, 20 GA (1mm) MS

SPECIFICATIONS	Imperial	Metric
Bed Width	40"	1016mm
Shear Capacity	20ga (.0359")	1mm
Bending Capacity	20ga (.0359")	1mm
Rolling Capacity	20ga (.0359")	1mm
Max Bend Angle	90°	
Min. Rolling Diameter	1.7"	43mm
Power Requirement	Manual	
Shipping Dimensions (L/W/H)	53"/18"/27"	1346mm/457mm/686mm
Shipping Weight	467Lbs	212Kg
Box Depth	4"	102mm

Specifications subject to change without notice.

- Bench-mounted
- Adjustable and removable 1-piece hardened fingers
- Extremely rigid frame
- Adjustable handles for increased leverage
- Forming grooves for solid rod applications



Wire Grooves