

TN-800

Tube & Pipe Notcher
Eccentric Cut



Set to desired OD. Turn hand wheel counter-clockwise. One revolution per weld joint.

One Tool
25mm to 76mm



SPECIFICATIONS

	Imperial	Metric
Mild Steel Pipe (Sch. 40)	2.5"	73mm
Aluminium Pipe (Sch. 40)	2.5"	73mm
Stainless Steel Pipe (Sch. 40)	2.5"	73mm
Mild Steel Round Tube	3"	76mm
Aluminium Round Tube	3"	76mm
Chromolly Round Tube	3"	76mm
Mild Steel Solid Rod	3"	76mm
Mild Steel Square Rod	3"	76mm
Minimum OD	0.50"	13mm
Power Requirements	240V, Single Phase, 50 Hz	
Weight	610 Lbs	280 Kg
Height	48"	1219mm
Width	44"	1118mm
Length	60"	1524mm
Motor Size	.5HP	.4kw
RPM	177rpm	
Angle Adjust	0-60°	
End Mill Spec	25mm x 165mm (100mm Cutting Surface)	
Notching Range	0.5" to 3"	13mm to 76mm

Specifications subject to change without notice.

No tooling changes up to 25mm to 76mm OD
Perfect weld joint
13mm min. / 76mm max. capacity
Angles and offsets
Fast and clean
220V, Single Phase, 50Hz
Patent No: 6,435,783